

# 4 MP PTZ Network Camera

30x IR PTZ Network Camera



- 1/3-in. 4 MP Progressive-scan CMOS
- Powerful 30x Optical Zoom
- Triple Stream Encoding, Maximum 4 MP, 3 MP at 30 fps
- H.265 and H.264 Dual Codec
- True Wide Dynamic Range
- Auto-tracking and Intelligent Video System (IVS)
- Maximum IR Distance up to 100 m (328 ft)
- IP66 Environmental Protection Rating
- PoE+ Support
- Five-year Warranty\*



## System Overview

The 4 MP IR PTZ Dome camera features a 1/3-in CMOS imager with a 30x optical zoom lens, and provides an all in one solution for capturing long-distance video surveillance for outdoor applications. The camera uses the Smart H.265+ video compression standard to improve encoding efficiency while preserving high-quality video. The PTZ camera is equipped with quick and accurate pan/tilt/zoom control and True WDR for applications with direct sunlight or glare.

## Functions

### Wide Dynamic Range

The camera achieves vivid images, even in the most intense contrast lighting conditions, using industry-leading wide dynamic range (WDR) technology. For applications with both bright and low lighting conditions that change quickly, True WDR (120 dB) optimizes both the bright and dark areas of a scene at the same time to provide usable video.

### Intelligent Video System (IVS)

IVS is a built-in video analytic algorithm that delivers intelligent functions to monitor a scene for Tripwire violations, intrusion detection, and abandoned or missing objects. A camera with IVS quickly and accurately responds to monitoring events in a specific area. In addition to scene analytics, the camera supports face detection to quickly capture a face and upload the image to a server. The camera also offers tamper detection by recognizing a dramatic scene change and generating a warning message to inspect the camera.

### Defog

Utilizing Dahua's advanced algorithm technology, the Defog feature dynamically adjusts the camera's contrast settings to provide improved image quality in scenes affected by fog, smog, mist, smoke or other low-contrast interference.

### Auto-tracking

This feature controls the pan/tilt/zoom actions of the camera to automatically track an object in motion and to keep it in the scene. The tracking action can be triggered manually or automatically by defined rules. Once a rule is triggered, the camera can zoom in and track the defined target automatically.

### PFA Technology

The camera uses innovative PFA Technology to improve zoom accuracy and to decrease focus time. A series of advanced algorithms more accurately judge the direction and the distance to a subject, improving picture clarity throughout the zooming process.

### Smart H.265+

Smart H.265+ is the optimized implementation of the H.265 codec that uses a scene-adaptive encoding strategy, dynamic GOP, dynamic ROI, flexible multi-frame reference structure and intelligent noise reduction to deliver high-quality video without straining the network. Smart H.265+ technology reduces bit rate and storage requirements by up to 70% when compared to standard H.265 video compression.

### Interoperability

The camera conforms to the ONVIF (Open Network Video Interface Forum) and to the PSIA (Physical Security Interoperability Alliance) specifications, ensuring interoperability between network video products regardless of manufacturer.

### Environmental

With a built-in heater and a temperature range of -40° C to +70° C (-40° F to 158° F), the camera is designed for extreme temperature environments. Subjected and certified to rigorous dust and water immersion tests, the IP66 rating makes it suitable for demanding outdoor applications.



Technical Specification			
Camera			
Image Sensor		1/3-in. CMOS	
Effective Pixels		2592(H) x 1520(V), 4 MP	
RAM/ROM		1024 MB / 128 MB	
Scanning System		Progressive	
Electronic Shutter Speed		1/1 s to 1/30,000 s	
Minimum Illumination		Color: 0.05 lux at F1.6 0 lux at F1.6 with IR on	
S/N Ratio		More than 55 dB	
IR Distance		Distance up to 100.0 m (328.10 ft)	
IR On/Off Control		Auto, Manual	
IR LEDs		Four (4)	
Lens			
Focal Length		4.5 mm to 135 mm	
Max. Aperture		F1.6 to F4.4	
Angle of View		Horizontal: 60° to 2.2°	
Optical Zoom		30x	
Focus Control		Auto, Manual	
Close Focus Distance		100 mm to 1000 mm	
DORI <sup>1</sup> Distance			
Detect (8 ppf)	Observe (19 ppf)	Recognize (38 ppf)	Identify (76 ppf)
2700 m (8858 ft)	1080 m (3543 ft)	540 m (1772 ft)	270 m (886 ft)
PTZ			
Pan/Tilt Range		Pan: 0° to 360° endless Tilt: -15° to 90°, Auto Flip 180°	
Manual Control Speed		Pan: 0.1° to 300° /s Tilt: 0.1° to 200° /s	
Preset Speed		Pan: 400° /s Tilt: 300° /s	
Presets		300	
PTZ Mode		5 Pattern, 8 Tour, Auto Pan, Auto Scan	
Speed Setup		Human-oriented Focal Length, Speed Adaptation	
Power up Action		Auto restore to previous PTZ and lens status after power failure	
Idle Motion		Activate Preset, Scan, Tour, or Pattern if there is no command in the specified period	
Protocol		DH-SD	
Video			
Compression		Smart H.265+, H.265, Smart H.264+, H.264	
Streaming Capability		Three (3) Streams	
Resolution		4 MP (2592 x 1520), 3 MP (2304 x 1296), 1080p (1920 x 1080), 720p (1280 x 720), D1 (704 x 480), CIF (352 x 240)	
Frame Rate	Main Stream	4 MP, 3 MP at 30 fps or 1080p, 1.3 MP, or 720p at 60 fps	
	Sub Stream 1	D1 or CIF at 30 fps	
	Sub Stream 2	1080p, 1.3 MP, 720p, D1 or CIF at 30 fps	

1. The DORI distance is a measure of the general proximity for a specific classification to help pinpoint the right camera for your needs. The DORI distance is calculated based on sensor specifications and lab test results according to EN 62676-4, the standard that defines the criteria for the Detect, Observe, Recognize and Identify classifications.

Bit Rate Control	CBR, VBR
Bit Rate	H.265/H.264: 448 K to 8192 Kbps
Day/Night	Auto (ICR), Color, B/W
Backlight Compensation	BLC, HLC, WDR (120 dB)
White Balance	Auto, ATW, Indoor, Outdoor, Manual
Gain Control	Auto, Manual
Noise Reduction	Ultra DNR (2D/3D)
Advanced Features	Motion Detection, Region of Interest, Electronic Image Stabilization (EIS), Defog
Digital Zoom	16x
Flip	180°
Privacy Masking	Up to 24 areas
Audio	
Compression	G.711a, G.711Mu, AAC, G.722, G.726, G.729, MPEG2-L2
Network	
Ethernet	RJ-45 (10 Base-T/100 Base-TX)
Protocol	IPv4/IPv6, HTTP, HTTPS, SSL, TCP/IP, UDP, UPnP, ICMP, IGMP, SNMP, RTSP, RTP, SMTP, NTP, DHCP, DNS, PPPOE, DDNS, FTP, IP Filter, QoS, Bonjour, 802.1x
Interoperability	ONVIF, PSIA, CGI
Streaming Method	Unicast, Multicast
Max. User Access	20 users
Edge Storage	NAS (Network Attached Storage) Local PC for instant recording, Micro SD Card, maximum 128 GB
Web Viewer	IE 10, Firefox, Safari
Management Software	Smart PSS, DSS
Mobile Operating System	iOS, Android
Certifications	
CE	EN 55032 EN 55024 EN 50130-4
UL	UL: UL60950-1 + CAN/CSA C22.2, No.60950-1
Electromagnetic Compatibility (EMC)	FCC Part 15 Subpart B ANSI C63.4-2014
Interface	
Audio	Input: One (1) Channel Output: One (1) Channel
Alarm	Input: Two (2) Channels Output: One (1) Channel
Electrical	
Power Supply	24 VAC, 3 A (±10%), PoE+ (802.3at)
Power Consumption	13 W, 23 W with IR on

## Environmental

Operating Conditions	-40° C to 70° C (-40° F to +158° F), Less than 90% RH
Ingress Protection	IP66

## Construction

Casing	Metal
Dimensions	Ø186.0 mm x 309.0 mm (Ø7.32 in. x 12.17 in.)
Net Weight	3.50 kg (7.72 lb)
Gross Weight	6.80 kg (14.99 lb)

## Intelligence

IVS triggers an alarm and takes a defined action for the following events:

Standard Features	<ul style="list-style-type: none"> <li>Tampering with the camera.</li> <li>Error writing to an onboard Micro SD card.</li> <li>Error sending or receiving data over the network.</li> <li>Unauthorized access to the camera.</li> </ul>
Premium Features	
Motion	An object moves through any part of the scene.
Tripwire	A target crosses a user-defined line.
Intrusion	A target enters or exits a defined perimeter.
Scene Change	A person or object moves the camera to change the scene or covers the camera to obscure the scene.
Abandoned/Missing Object	A target leaves an object in designated area, or a target removes an object from the same designated area.
Advanced Features	
Facial Detection	Detects and captures a snapshot of a human face in a defined area within a scene.
Heat Map	Generates a visual representation of data.
Auto-tracking	Controls the pan/tilt/zoom actions of the camera to automatically track an object in motion and to keep it in the scene.

## Ordering Information

Type	Part Number	Description
4 MP PTZ Camera	59430UNI	4 MP 30x IR PTZ Network Camera, WDR, IVS
Accessories, included	AC24V/3A	Power Adapter
	PFA110	Mount Adapter
	PFB300S	Wall Mount
Accessories, optional	PFA120	Junction Box
	PFA140	Power Box
	PFA150	Pole Mount
	PFA151	Corner Mount
	PFB300C	Ceiling Mount
	PFB303S	Parapet Mount

## Accessories

## Included:



PFB300S  
Wall Mount



PFA110  
Mount Adapter



AC24V/3A  
Power Adapter

## Optional:



PFA140  
Power Box




PFB300C  
Ceiling Mount



PFA120  
Junction Box



PFA150  
Pole Mount



PFA151  
Corner Mount



PFB303S  
Parapet Mount

Ceiling Mount	Junction Mount
PFA110 + PFB300C	PFA110 + PFB300S + PFA120
Power Box Mount	Pole Mount
PFA110 + PFB300S + PFA140	PFA110 + PFB300S + PFA150
Corner Mount	Parapet Mount
PFA110 + PFB300S + PFA151	PFA110 + PFB303S

Dimensions (mm)

